

Pinnacle Risk Management Pty Limited ABN 83 098 666 703

14 November 2023

PO Box 5024 Elanora Heights NSW 2101

Telephone: (61 2) 9913 7284 Facsimile: (61 2) 9913 7930 Email: deanshewring@optusnet.com.au

BESIXWatpac

# Subject: Moree Hospital, State Environmental Planning Policy (Resilience and Hazards) 2021, Part 3, SEPP 33

It is proposed to increase the number of medical gas cylinders stored at Moree Hospital. As part of the assessment process, an "Applying SEPP 33" analysis is required.

A site layout drawing showing the existing and proposed Dangerous Goods stores is shown in Attachment 1.

The Applying SEPP 33 analysis is shown in Attachment 2.

The facility is currently a potentially hazardous facility as the quantity of LPG stored on the site exceeds the SEPP 33 criterion of 10 te. The proposed changes, however, do not increase the quantity of LPG storage. As shown in the site layout drawing in Attachment 1, the existing LPG tanks are suitably located away from the existing and proposed cylinder stores. It is assumed that the existing facility is currently approved.

The other Dangerous Goods stored at the facility include oxygen (as liquid in a tank and gas in cylinders), Nitronox (a mixture of oxygen and nitrous oxide in cylinders) and nitrous oxide (in cylinders). These are subsidiary class 5.1 substances. The total storage quantity of this Dangerous Goods class is 4.72 te. This is the combined quantity from the existing and proposed stores. As this is less than the SEPP 33 criterion of 5 te and the transport frequencies are significantly less than the SEPP 33 criteria then these substances are not deemed to be potentially hazardous. There are also no credible propagation events between the LPG tanks and the various Dangerous Goods class 5.1 stores that would lead to any unacceptable off-site risks. Correspondingly, a Preliminary Hazard Analysis (PHA) is not recommended for this project.

There are no other known hazardous materials associated with the project that would deem the facility to be a potentially hazardous facility, e.g. combustible dust.

Yours sincerely,

D Shewring

Dean Shewring Principal Risk Consultant

#### Attachment 1 Site Layout Drawing



#### Pinnacle Risk Management



### Attachment 2 Applying SEPP 33 Analysis

Dangerous Good / Materials	DG Class	DG Subsidiary Risk	Storage Quantity (te)	SEPP 33 Threshold Value	Transport Frequency	Mode of Transport	SEPP 33 Threshold Transport Frequency	Is a PHA Required:	Comme
DG Class 2.1:									
Existing LPG (3x 7.5 m3 aboveground tanks)	2.1	-	13	10 te	Once every 2 weeks	Tankers	30/week and the load needs to be >2 te (Table 2)		This stor however not incre also loca developr
DG Class 5.1									
Existing Oxygen (2.75 m3 liquid storage tank)	2.2	5.1	3.1	5 te	Once every 8 weeks (typically 1.8 te)	Tanker	30/week and the load needs to be >2 te (Table 2)	No	DG 2.2 is included approxin good set
Existing Cylinders:									
BOC Emergency Oxygen (10x G size cylinders)	2.2	5.1	0.112		0		30/week and the load needs to be >5 te (Table 2)		Emerger
LAA Medical Oxygen (10x E size cylinders)	2.2	5.1	0.057		2 cylinders per month		30/week and the load needs to be >5 te (Table 2)		
LAA Medical Oxygen (48x CH size cylinders)	2.2	5.1	0.030		9 cylinders per month		30/week and the load needs to be >5 te (Table 2)		
LAA Nitronox (6x E size cylinders)	2.2	5.1	0.041		1 cylinder per month		30/week and the load needs to be >5 te (Table 2)		
LAA Nitronox (1x C size cylinders)	2.2	5.1	0.001		Typically 0		30/week and the load needs to be >5 te (Table 2)		
LAA Nitrous oxide (10x G size cylinders)	2.2	5.1	0.322		3 cylinders per month		30/week and the load needs to be >5 te (Table 2)		
LAA Nitrous oxide (4x C size cylinders)	2.2	5.1	0.007		Typically 0		30/week and the load needs to be >5 te (Table 2)		
Total:			0.571						
		1							

nts
age exceeds the SEPP33 criterion of 10 te.
it is existing. The proposed modifications do
ase the storage of DG 2.1 The LPG tanks are
ted approximately 100 m from the new
nent, i.e. good separation distance
,
s excluded from the risk screening. DG 5.1 is
in the risk screening. The tank is located
nately 30 m from the closest cylinder store, i.e.
paration distance
ncy use only

DG Subsidiary Risk	Storage Quantity (te)	SEPP 33 Threshold Value	Transport Frequency	Mode of Transport	SEPP 33 Threshold Transport Frequency	Is a PHA Required:	Comme
5.1	0.505		Once per year		30/week and the load needs to be >5 te (Table 2)		
5.1	0.386		Once every 3 months		30/week and the load needs to be >5 te (Table 2)		
5.1	0.057		Once every 2 weeks		30/week and the load needs to be >5 te (Table 2)		
5.1	0.041		Once every 2 weeks		30/week and the load needs to be >5 te (Table 2)		
5.1	0.001		Once every 2 weeks		30/week and the load needs to be >5 te (Table 2)		
5.1	0.007		Once every 2 weeks		30/week and the load needs to be >5 te (Table 2)		
5.1	0.030		Once every 2 weeks		30/week and the load needs to be >5 te (Table 2)		
	1.028						
5.4	0.000						
5.1	0.022		Once every year		30/week and the load needs to be >5 te (Table 2)		
	4 72	5 to				No	
	DG   Subsidiary   5.1   5.1   5.1   5.1   5.1   5.1   5.1   5.1   5.1   5.1   5.1   5.1   5.1   5.1   5.1   5.1   5.1   5.1	DG     Storage Quantity (te)       5.1     0.505       5.1     0.386       5.1     0.057       5.1     0.041       5.1     0.001       5.1     0.001       5.1     0.001       5.1     0.001       5.1     0.001       5.1     0.001       5.1     0.002       5.1     0.022       5.1     0.022	DG Subsidiary Risk     Storage Quantity (te)     Sterp 33 Threshold Value       5.1     0.505       5.1     0.505       5.1     0.386       5.1     0.057       5.1     0.001       5.1     0.001       5.1     0.001       5.1     0.007       5.1     0.030       5.1     0.030       5.1     0.022       5.1     0.022	DG Subsidiary RiskStorage Quantity (te)Storage Threshold ValueTransport Frequency5.10.505Once per year5.10.386Once every 3 months5.10.057Once every 2 weeks5.10.041Once every 2 weeks5.10.001Once every 2 weeks5.10.001Once every 2 weeks5.10.001Once every 2 weeks5.10.001Once every 2 weeks5.10.007Once every 2 weeks5.10.007Once every 2 weeks5.10.022Once every 2 weeks5.10.022Once every 2 weeks	DG Subsidiary RiskStorage Quantity (te)Sterp 33 Threshold ValueTransport FrequencyMode of Transport5.10.505Once per year5.10.386Once every 3 months5.10.057Once every 2 weeks5.10.041Once every 2 weeks5.10.001Once every 2 weeks5.10.007Once every 2 weeks5.10.007Once every 2 weeks5.10.007Once every 2 weeks5.10.007Once every 2 weeks5.10.007Once every 2 weeks5.10.007Once every 2 weeks5.10.022Once every 2 weeks	DG Subsidiary RiskStorage Quantity (te)Storage Threshold ValueStepP 33 	DG Subsidiary RiskStorage Quantity (te)StepP 33 TransportTransport TransportStepP 33 TransportTransport Required:5.10.505Once per year30/week and the load needs to be >5 te (Table 2)5.10.386Once every 3 months30/week and the load needs to be >5 te (Table 2)5.10.057Once every 2 weeks30/week and the load needs to be >5 te (Table 2)5.10.041Once every 2 weeks30/week and the load needs to be >5 te (Table 2)5.10.041Once every 2 weeks30/week and the load needs to be >5 te (Table 2)5.10.001Once every 2 weeks30/week and the load needs to be >5 te (Table 2)5.10.001Once every 2 weeks30/week and the load needs to be >5 te (Table 2)5.10.001Once every 2 weeks30/week and the load needs to be >5 te (Table 2)5.10.002Once every 2 weeks30/week and the load needs to be >5 te (Table 2)5.10.030Once every 2 weeks30/week and the load needs to be >5 te (Table 2)5.10.030Once every 2 weeks30/week and the load needs to be >5 te (Table 2)5.10.022Once every 2 weeks30/week and the load needs to be >5 te (Table 2)5.10.022Once every year30/week and the load needs to be >5 te (Table 2)5.10.022Once every year30/week and the load needs to be >5 te (Table 2) </td

## Pinnacle Risk Management

ents	